

```
!
version 12.3
no service pad
service timestamps debug datetime msec
service timestamps log datetime msec
service password-encryption
!
hostname skaiap1
!
enable secret 5 $1$WYUY$leqtpwMXZKMuCaFmTdAFi/
!
username Cisco password 7 0802455D0A16
ip subnet-zero
!
aaa new-model
!
!
aaa group server radius rad_eap
  server 10.0.1.1 auth-port 1645 acct-port 1646
!
aaa group server radius rad_mac
!
aaa group server radius rad_acct
!
aaa group server radius rad_admin
!
aaa group server tacacs+ tac_admin
!
aaa group server radius rad_pmip
!
aaa group server radius dummy
!
aaa authentication login eap_methods group rad_eap
aaa authentication login mac_methods local
aaa authorization exec default local
aaa accounting network acct_methods start-stop group rad_acct
aaa session-id common
!
!
bridge irb
!
!
interface Dot11Radio0
  no ip address
  no ip route-cache
!
  encryption vlan 3 mode wep mandatory
!
  ssid skai
    vlan 3
    authentication open eap eap_methods
    authentication network-eap eap_methods
!
  speed basic-1.0 basic-2.0 basic-5.5 basic-11.0
  station-role root
  no cdp enable
  bridge-group 1
  bridge-group 1 subscriber-loop-control
  bridge-group 1 block-unknown-source
  no bridge-group 1 source-learning
```

```
no bridge-group 1 unicast-flooding
bridge-group 1 spanning-disabled
!
interface Dot11Radio0.3
  encapsulation dot1Q 3
  no ip route-cache
  bridge-group 3
  bridge-group 3 subscriber-loop-control
  bridge-group 3 block-unknown-source
  no bridge-group 3 source-learning
  no bridge-group 3 unicast-flooding
  bridge-group 3 spanning-disabled
!
interface FastEthernet0
  no ip address
  no ip route-cache
  duplex auto
  speed auto
  bridge-group 1
  no bridge-group 1 source-learning
  bridge-group 1 spanning-disabled
!
interface FastEthernet0.3
  encapsulation dot1Q 3
  no ip route-cache
  bridge-group 3
  no bridge-group 3 source-learning
  bridge-group 3 spanning-disabled
!
interface BVI1
  ip address dhcp client-id FastEthernet0
  no ip route-cache
!
ip http server
no ip http secure-server
ip http help-path
http://www.cisco.com/warp/public/779/smbiz/prodconfig/help/eag
ip radius source-interface BVI1
logging snmp-trap emergencies
logging snmp-trap alerts
logging snmp-trap critical
logging snmp-trap errors
logging snmp-trap warnings
radius-server attribute 32 include-in-access-req format %h
radius-server host 10.0.1.1 auth-port 1645 acct-port 1646 key 7
02350F5A02394A701F62061E0C04060207497D68050F
radius-server vsa send accounting
bridge 1 route ip
!
!
!
line con 0
  transport preferred all
  transport output all
line vty 0 4
  transport preferred all
  transport input all
  transport output all
line vty 5 15
  transport preferred all
  transport input all
```

```
transport output all
!
end
```